

ATE5 Chapter 109 TIRES & WHEELS

Opening Your Class

KEY ELEMENT	EXAMPLES
Introduce Content	This course or class provides complete coverage of the components, operation, design, and troubleshooting. It correlates material to task lists specified by ASE and NATEF and emphasizes a problem-solving approach. Chapter features include Tech Tips, Frequently Asked Questions, Real World Fixes, Videos, Animations, and NATEF Task Sheet references.
Motivate Learners	Explain how the knowledge of how something works translates into the ability to use that knowledge to figure why the engine does not work correctly and how this saves diagnosis time, which translates into more money.
State the learning objectives for the chapter or course you are about to cover and explain this is what they should be able to do as a result of attending this session or class.	Explain learning objectives to students as listed below: <ol style="list-style-type: none">1. Identify the parts of a tire.2. Discuss tire sizes and speed ratings.3. Describe tire selection considerations.4. Explain the construction and sizing of steel and alloy wheels and attaching hardware.5. Demonstrate correct lug nut tightening procedure and torque.
Establish the Mood or Climate	Provide a WELCOME , Avoid put downs and bad jokes.
Complete Essentials	Restrooms, breaks, registration, tests, etc.
Clarify and Establish Knowledge Base	Do a round robin of the class by going around the room and having each student give their backgrounds, years of experience, family, hobbies, career goals, or anything they want to share.

NOTE: This lesson plan is based on the 5th Edition Chapter Images found on Jim's web site @

www.jameshalderman.com

LINK CHP 109: [ATE5 Chapter Images](#)

ICONS



Chapter 109 Tires & Wheels

1. SLIDE 1 CH109 TIRES & WHEELS

Check for ADDITIONAL VIDEOS & ANIMATIONS @
<http://www.jameshalderman.com/>
WEB SITE IS CONSTANTLY UPDATED

Videos

2. SLIDE 2 EXPLAIN Figure 109-1 (a) typical tire tread depth gauge. The center movable plunger is pushed down into the groove of the tire.
3. SLIDE 3 EXPLAIN Figure 109-1 (b) tread depth is read at the top edge of the sleeve. In this example, the tread depth is 6/32 in.

DEMONSTRATION: Show typical tread depth gauge. explain how to use it, **SEE FIGURE 109-1**

DISCUSSION: Discuss other possible symptoms of bad or defective tires. Discuss the importance of tread depth and to discuss why all tire manufacturers don't use the same standard **depth.**

HANDS-ON TASK: Have the students use a tread depth gauge to measure tread depth. Ask them to read you the gauge and indicate depth of tread.

4. SLIDE 4 EXPLAIN Figure 109-2 Wear indicators (wear bars) are strips of bald tread that show when tread depth is down to 2/32 in., legal limit in many states.

DEMONSTRATION: Show the students examples of tires with wear bars, **FIGURE 109-2**

DISCUSSION: Discuss whether there is a generally accepted practice regarding repair of tires with sidewall punctures. Discuss why it is necessary to replace a tire if the tire's bead is cut or damaged. Discuss which are stronger: bias-ply tires or radial-ply tires.

ICONS



Chapter 109 Tires & Wheels

HANDS-ON TASK: Using a tire crayon, have students circle wear bars on both new & used tires.

- 5. SLIDE 5 EXPLAIN Figure 109-3** tire tread runs around the circumference of the tire, and its pattern helps maintain traction. The ribs provide grip, while the grooves direct any water on the road away from the surface. The sipes help the tire grip the road.
- 6. SLIDE 6 EXPLAIN Figure 109-4** Hydroplaning can occur at speeds as low as 30 mph (48 km/h). If the water is deep enough and the tire tread cannot evacuate water through its grooves fast enough, the tire can be lifted off the road surface by a layer of water. Hydroplaning occurs at lower speeds as the tire becomes worn.
- 7. SLIDE 7 EXPLAIN Figure 109-5** Typical construction of a radial tire. Some tires have only one body ply, and some tires use more than two belt plies.
- 8. SLIDE 8 EXPLAIN Figure 109-6** The major splice of a tire can often be seen and felt on the inside of the tire. The person who assembles (builds) the tire usually places a sticker near the major splice as a means of identification for quality control.

DEMONSTRATION: Using both new and used tires, show the students the major Splice.

DISCUSSION: Ask the students to discuss why damage to the inner liner will cause a flat tire.

- 9. SLIDE 9 EXPLAIN Figure 109-7** Tire construction is performed by assembling the many parts of a tire together on a tire-building machine.
- 10. SLIDE 10 EXPLAIN Figure 109-8** After the entire tire has been assembled into a completed “green” tire, it is placed into a tire-molding machine where the tire is molded into shape and the rubber is changed chemically by the heat. This nonreversible chemical reaction is called vulcanization

DISCUSSION: discuss problems that would develop by using a space-saving spare tire over an extended period of time.

ICONS



Chapter 109 Tires & Wheels

11. **SLIDE 11 EXPLAIN FIGURE 109-9** Notice that the overall outside diameter of the tire remains almost the same and at the same time the aspect ratio is decreased and the rim diameter is increased.

12. **SLIDE 12 EXPLAIN Figure 109-10** Cross-sectional view of a typical tire showing the terminology.

DEMONSTRATION: Show how to decode several tire sizes using service description. **FIGURE 109-10**

HANDS-ON TASK: Have students decode several tire sizes using service description. **FIG. 109-10**

When changing from an older tire measuring system to a newer system, speedometer calibration should be checked.

DEMONSTRATION: show how to decode the Metric tire coding and explain it

HANDS-ON TASK: Have students decode several metric tire sizes.

13. **SLIDE 13 EXPLAIN Figure 109-11** Typical sidewall markings for load index & speed rating following tire size.

DISCUSSION: Ask the students whether using tires with suffix LT (Light Truck) page 1245 is acceptable on passenger cars and/or SUVs.

DISCUSSION: Ask the students to discuss the advantages, if any, of using radial tires on an older automobile.

DISCUSSION: Ask the students how changing the section height will affect the ride quality

DISCUSSION: discuss why tires are made with H-speed ratings of 130 mph or 210 km/h despite the fact that driving that fast would not only be unsafe but also illegal in most areas of the world.

ICONS



Chapter 109 Tires & Wheels

DISCUSSION: Ask the students to compare DOT standards & E.C.E. (Economic Commission for European Small “e”) standards. Ask students to discuss whether US should have anti-noise standards similar to E.C.E pass-by noise limits.

14. **SLIDE 14 EXPLAIN FIGURE 109-12** Light weight dense foam curved

ramps help keep tires from being flat-spotted while the vehicle is being stored.

15. **SLIDE 15 EXPLAIN Figure 109-13** typical door placard used on a GM vehicle indicating recommended tire inflation. Note that the information also includes the tire size and speed rating of the tire as well as the recommended wheel size

DEMONSTRATION: Show the students how to determine **proper tire pressure** by using the information on door placards.

HANDS-ON TASK: Have students compare tire pressure recommendations of several automobiles by using the information on door placards.

16. **SLIDE 16 EXPLAIN Figure 109-14** Conicity is a fault in the tire that can cause the vehicle to pull to one side due to the cone effect (shape) of the tire.


DEMONSTRATION: Using a foam cup, show the students how a cone shape will cause a **pull**.

17. **SLIDE 17 EXPLAIN Figure 109-15** Notice the angle of the belt material in this worn tire. The angle of the belt fabric can cause a “ply steer” or slight pulling force toward one side of the vehicle.

18. **SLIDE 18 EXPLAIN Figure 109-16** Slip angle is the angle between the direction the tire tread is heading and the direction it is pointed.

DISCUSSION: Ask the students to discuss how tread depth and aspect ratio affect tire slip angle

ICONS



Chapter 109 Tires & Wheels

19. **SLIDE 19 EXPLAIN** Figure 109-17 typical “Uniform Tire Quality Grading System” (UTQGS) ratings imprinted on the tire sidewall

DISCUSSION: Ask the students to discuss whether people living in hot climates should purchase tires with **C Temperature** resistance rating.

DISCUSSION: Ask the students to discuss whether a tire’s tread wear rating number has any relationship to the price of the tire

Aligning a vehicle to correct for a bad tire will cause the pull to return when the tires are rotated.

20. **SLIDE 20 EXPLAIN** Figure 109-18 Typical DOT date code. This tire was built the sixth week of 2005.

21. **SLIDE 21 EXPLAIN FIGURE 109-19** Cutaway of a run-flat tire showing the reinforced sidewalls and the required pressure sensor.

DISCUSSION: Ask the students to discuss how important DOT date code is when deciding to purchase a tire.

When installing aftermarket wheels using non-stock lug nuts, wire tie a set of stock lug nuts to the spare tire wheel

Many tire manufacturers require only returning the DOT code of the tire for claims on a warranty. This saves shipping cost.

Be sure to include checking spare tire mounting hardware as part of a general service.

22. **SLIDE 22 EXPLAIN** Figure 109-20 A conventional tire on the left and a run-flat tire on right, showing what happens when there is no air in the tire.

ICONS



Chapter 109 Tires & Wheels

DISCUSSION: Ask the students to discuss the advantages and disadvantages of using run-flat tires.

HANDS-ON TASK: Have the students use visual clues to identify run-flat tires on vehicles.

23. **SLIDE 23 EXPLAIN** Figure 109-21 PAX run-flat tire system is composed of 3 unique components: special asymmetrical wheel, urethane support ring, & special tire.
24. **SLIDE 24 EXPLAIN** Figure 109-22 The Tire Performance Criteria (TPC) specification number is imprinted on the sidewall of all tires used on General Motors vehicles from the factory.

DEMONSTRATION: Show the students how to read and interpret the **Tire Performance Criteria (TPC) specification number** on a tire standard on a **General Motors** vehicle.

HANDS-ON TASK: Have the students find TPC numbers on several tires on GM Lab or Personal Vehicle

DISCUSSION: Have the students discuss why rolling resistance is a concern on hybrid vehicles.

25. **SLIDE 25 EXPLAIN** Figure 109-23 The size of the wheel is usually cast or stamped into the wheel. This wheel is 7 inches wide. The letter “J” refers to the contour of the bead seat area of the wheel.
26. **SLIDE 26 EXPLAIN** Figure 109-24 The wheel rim well provides a space for the tire to fit during mounting; the bead seat provides a tire-to-wheel sealing surface; the flange holds the beads in place.
27. **SLIDE 27 EXPLAIN** Figure 109-25 A cross section of a wheel showing part designations.
28. **SLIDE 28 EXPLAIN** Figure 109-26 Offset is the distance between the centerline of the wheel and the wheel mounting surface

ICONS



Chapter 109 Tires & Wheels

29. **SLIDE 29 EXPLAIN** Figure 109-27 Back spacing (rear spacing) is the distance from the mounting pad to the edge of the rim. Most custom wheels use this measurement method to indicate the location of the mounting pad in relation to the rim.

DEMONSTRATION: Show the students examples of several wheels and explain how to determine the size of wheel and the exact shape of flange area.

DISCUSSION: Ask the students to discuss why the flange area shape and the angle that the rim drops down from the flange are important.

HANDS-ON TASK: Have the students use sticky notes or masking tape to label the parts of the rim.

30. **SLIDE 30 EXPLAIN** Figure 109-28 Bolt circle is the diameter of a circle that can be drawn through the center of each lug hole or stud. The bolt circle is sometimes referred to as PCD for pitch circle diameter.

31. **SLIDE 31 EXPLAIN** Figure 109-29 Measuring the bolt circle on a five lug wheel is difficult, but a quick and easy way includes measuring as shown to determine the approximate bolt circle of a five-lug wheel

DEMONSTRATION: Show the students how to use a tape measure to determine approximate bolt circle of a 5-lug wheel, **FIGURE 109-29**

HANDS-ON TASK: Have the students use tape measures to determine the approximate bolt circles of five-lug wheels, **FIGURE 109-29**

Most tire shops have bolt circle templates. The templates have several bolt circles on them. This makes it faster to identify a bolt circle.

32. **SLIDE 32 EXPLAIN** Figure 109-30 Measure center-to-center distance and compare the distance to the figures in the chart in the text to determine the diameter for a five-lug bolt circle.

ICONS



Chapter 109 Tires & Wheels

33. SLIDE 33 EXPLAIN FIGURE 109.31 typical JWL symbol for the Japan Wheel Light Metal standard mark.
34. SLIDE 34 EXPLAIN Figure 109-32 (a) A rubber snap-in style tire valve assembly. (b) A metal clamp-type tire valve assembly used on most high pressure (over 60 PSI) tire applications such as is found on many trucks, RVs, and trailers. The internal Schrader valve threads into the valve itself and can be replaced individually, but most experts recommend replacing entire valve assembly every time tires are replaced to help prevent air loss.

Racers quote a 4:1 ratio gain in removing UNSPRUNG WEIGHT. As an example, removing 25 lb of unsprung weight would have the same effect on handling as removing 100 lb of sprung weight.

35. SLIDE 35 EXPLAIN Figure 109-33 Various styles of lug nuts

DEMONSTRATION: Show the students various types of lug nuts and explain why there are different types. FIGURE 109-33

DISCUSSION: Ask the students to discuss why some OEMs use lug nuts and other manufacturers use lug bolts. FIGURE 109-33

HANDS-ON TASK: Have the students inspect tires on an assigned vehicle.

36. SLIDES 36-44 EXPLAIN OPTIONAL TIRE INSPECTION

ON-VEHICLE NATEF TASK: Research applicable vehicle and service information, such as suspension and steering system operation, vehicle history, service precautions, & TSBs. Pg 331

SEARCH INTERNET Have the students search the Internet to research the process of vulcanization. Ask them to prepare to report on vulcanization and its importance to the automotive industry during the next class.

ICONS



Chapter 109 Tires & Wheels

[Crossword Puzzle \(Microsoft Word\) \(PDF\)](#)

[Word Search Puzzle \(Microsoft Word\) \(PDF\)](#)