


Under Hood Vehicle Inspection

Chapter 17



<http://jameshaldeman.com>

ACROSS

- 4 The DOT 5 type is commonly called _____.
- 6 _____ brake fluid does not mix with and should not be used with DOT 3 or DOT 4 brake fluid.
- 8 While the additive packages and _____ varies, ATF is grouped in three basic types.
- 9 The oil level indicator, commonly called a _____, is clearly marked and in a convenient location.
- 11 _____ means periodic service work performed on a vehicle that will help keep it functioning correctly for a long time.

- 12 It is generally recommended that all belts, including the _____ belts be replaced every four to seven years.
- 14 The fluid used in hydraulic clutch _____ is DOT 3 brake fluid.
- 15 The _____ levels should be checked while the engine is running and at normal operating temperature.

DOWN

- 1 The _____ brake fluid is most often used.
- 2 A _____ is used in the heating, ventilation, and air-conditioning system to filter the

outside air drawn into the passenger compartment.

- 3 An _____ filters dirt from the air before it enters the intake system of the engine.
- 5 All _____ brake fluid is clear or amber in color.
- 7 The _____ brake fluid is a non-silicone-based polyglycol fluid that is clear to amber in color.
- 10 _____ is used to transmit the force of the driver's foot on the brake pedal to each individual wheel brake.
- 13 The _____ brake fluid is formulated for use by all vehicles, imported or domestic.