

# Service and Replace the Battery

Meets NATEF Task: (A6-B-4) Inspect, clean, fill, and replace the battery. (P-2)

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

\_\_\_\_\_ 1. Check service information for the specified procedures to follow to inspect, clean, fill, and replace a battery.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_ 2. Check all that apply:

- \_\_\_\_\_ Battery hold-down clamps/brackets are in place.
- \_\_\_\_\_ Filler cap(s) is(are) removable.
- \_\_\_\_\_ Battery electrolyte cannot be checked.
- \_\_\_\_\_ Electrolyte level is low.
- \_\_\_\_\_ Corrosion was found on battery terminals/cable ends.
- \_\_\_\_\_ Other faults or conditions (describe)

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_ 3. Clean the battery.

\_\_\_\_\_ 4. Clean the battery cables and cable ends.

\_\_\_\_\_ 5. Remove and install the battery.

