



Cylinder Power Balance Tests

Meets NATEF Task: (A8-A-9) Perform cylinder power balance tests; determine necessary action (P-2)

Name _____ Date _____ Time on Task _____

Make/Model/Year _____ VIN _____ Evaluation: 4 3 2 1

_____ 1. An automotive diagnostic scope or digital storage oscilloscope with relative compression can be used to determine cylinder balance. Check all that apply.

- _____ Automotive diagnostic scope
- _____ Digital storage oscilloscope with relative compression capability
- _____ Other (describe) _____

_____ 2. Follow the equipment manufacturers' instructions and connect the tester to the engine. Instructions to connect to the engine include: _____

_____ 3. Start the engine and allow it to reach normal operating temperature.

_____ 4. Follow the instructions of the test equipment manufacturer and perform a cylinder power balance test. Record the results.

Cylinder #1 = _____	Cylinder #5 = _____
Cylinder #2 = _____	Cylinder #6 = _____
Cylinder #3 = _____	Cylinder #7 = _____
Cylinder #4 = _____	Cylinder #8 = _____

_____ 5. If performing an engine speed (RPM) drop test, all cylinders should be within 50 RPM.

- _____ **OK**
- _____ **NOT OK** (describe results) _____
- _____ **NA**

_____ 6. If relative compression is being performed, all cylinders should be within 10%.

- _____ **OK**
- _____ **NOT OK** (describe results) _____
- _____ **NA**