

# Drive Axle Shaft Service

**Meets NATEF Task:** (A3-E-3-3, A3-E-3-4, A3-E-3-5) Remove and replace drive axle shafts.  
(P-1, P-2, P-2)

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

\_\_\_\_\_ 1. Check service information for the specified procedure to follow when inspecting and replacing drive axle shafts. Describe specified procedure. \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_



\_\_\_\_\_ 2. List the tools required. Check all that apply:

- \_\_\_\_\_ Lug nut wrench
- \_\_\_\_\_ Torque wrench
- \_\_\_\_\_ Spindle nut socket
- \_\_\_\_\_ CV boot protector
- \_\_\_\_\_ Axle puller
- \_\_\_\_\_ Other (describe) \_\_\_\_\_

\_\_\_\_\_ 3. Inspect bearings, seals, and retainers. \_\_\_\_\_

\_\_\_\_\_ 4. Measure drive axle flange runout. What is the necessary action? \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_