



# Bleed ABS Hydraulic Circuits

**Meets NATEF Task:** (A5-G-7) Bleed electronic brake control system hydraulic circuits. (P-1)

---

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

ABS hydraulic front and rear hydraulic circuits must be bled using the exact procedure specified by the vehicle manufacturer.

\_\_\_\_\_ 1. Check the service information and state the vehicle manufacturer's specified bleeding procedure and sequence.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_ 2. Type of brake fluid specified for use during the bleeding procedure?

\_\_\_\_\_

\_\_\_\_\_ 3. Was a scan tool required? \_\_\_\_ Yes \_\_\_\_ No If yes, describe the procedure:

\_\_\_\_\_

\_\_\_\_\_ 4. Was a special tool or tools required? \_\_\_\_ Yes \_\_\_\_ No If yes, describe the procedure:

\_\_\_\_\_

\_\_\_\_\_ 5. Was the bleeding procedure the same for both the front and the rear wheel brakes?

\_\_\_\_ Yes \_\_\_\_ No