



# Brake Hose and Line Inspection

**Meet NATEF Task:** (A5-B-3) Inspect brake lines and flexible hose for faults and determine necessary action. (P-1)

---

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

- \_\_\_\_\_ 1. Hoist the vehicle safely.
- \_\_\_\_\_ 2. Remove all four wheels.
- \_\_\_\_\_ 3. Carefully inspect the flexible brake hoses on the left front, right front, and rear (one or two flexible hoses) for the following:
  - \_\_\_\_\_ Leaks **OK** \_\_\_ **NOT OK** \_\_\_ Which hose(s)? \_\_\_\_\_
  - \_\_\_\_\_ Kinks **OK** \_\_\_ **NOT OK** \_\_\_ Which hose(s)? \_\_\_\_\_
  - \_\_\_\_\_ Cracks **OK** \_\_\_ **NOT OK** \_\_\_ Which hose(s)? \_\_\_\_\_
  - \_\_\_\_\_ Bulges or wear **OK** \_\_\_ **NOT OK** \_\_\_ Which hose(s)? \_\_\_\_\_
- \_\_\_\_\_ 4. Carefully inspect the steel brake lines from the master cylinder to the junction with the flexible brake lines and check for the following:
  - \_\_\_\_\_ Leaks **OK** \_\_\_ **NOT OK** \_\_\_ Fault location? \_\_\_\_\_
  - \_\_\_\_\_ Dents **OK** \_\_\_ **NOT OK** \_\_\_ Fault location? \_\_\_\_\_
  - \_\_\_\_\_ Loose fittings or supports **OK** \_\_\_ **NOT OK** \_\_\_  
Fault location? \_\_\_\_\_
- \_\_\_\_\_ 5. Based on the inspection, what is the necessary action? \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_