

# Drain and Replace Fluid and Filter(s)

Meets NATEF Task: (A2-B-4) Drain and replace fluid and filter(s). (P-1)

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

\_\_\_\_\_ 1. Check service information for the specified procedure to follow to drain and replace the fluid in an automatic transmission/transaxle. Describe the specified procedure.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_ 2. What is the specified fluid required? \_\_\_\_\_

\_\_\_\_\_ 3. How many quarts (liters) are required? \_\_\_\_\_

\_\_\_\_\_ 4. Check all that apply:

- \_\_\_\_\_ Uses an external filter
- \_\_\_\_\_ Uses an internal filter
- \_\_\_\_\_ Filter is accessible
- \_\_\_\_\_ Transmission/transaxle has a drain plug
- \_\_\_\_\_ Other (specify) \_\_\_\_\_

\_\_\_\_\_ 5. Loosen the pan, drain and then remove the transmission/transaxle pan.

\_\_\_\_\_ 6. Check the bottom of the pan for abnormal (metallic) debris.

\_\_\_\_\_ **OK** \_\_\_\_\_ **NOT OK**

\_\_\_\_\_ 7. Install a new gasket, install the pan, torque the fasteners to factory specification.

\_\_\_\_\_ 8. Install the fluid and check the level.

