Ignition Scope Analysis

Meets NATEF Task: (A8-C-1) P-2 Inspect and test ignition primary and secondary circuit wiring and solid state components; test ignition coil(s); perform necessary action.

| Name | Date _ | | Time on Tasl | <u> </u> | |
|---|--|-------------|------------------------|---------------|--------|
| Make/Model/Year | VIN | | Evaluation | : 4 3 | 2 1 |
| 1. Check service infor | | 20 KV | | | 4 |
| | or attaching and using | | | | |
| a secondary circui | oscilloscope. | 15 KV | | | 3 |
| | | | | | |
| | | I | FIRING | | |
| | | 10 KV | SPARK LINE | | 2 |
| 2. Type of ignition: | | | (SPARK DURATION) | I DW | ELL |
| | | 5 KV | SECTION | SEC | TION 1 |
| Distribu | utor | | Mar | - | |
| Waste s | • | | 100 | | |
| Coil-on | -plug | 0 KV Li | 1 mS 2 mS 3 | mS 4 m | S 5 mS |
| | n scope to the system as | - | - | r's | |
| 3. Connect the ignition instructions.4. Brand of scope used | | | | _ | |
| 3. Connect the ignition instructions.4. Brand of scope used5. Describe the hooku | d: | | | _ | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and | d:p procedure | ignition wa | | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol | d: p procedure d observe the secondary Firing Voltage (KV) | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol.) Cylinder #1 | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol Cylinder #1 Cylinder #2 Cylinder #3 Cylinder #4 | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol Cylinder #1 Cylinder #2 Cylinder #3 Cylinder #4 Cylinder #5 | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol Cylinder #1 Cylinder #2 Cylinder #3 Cylinder #4 Cylinder #5 Cylinder #6 | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |
| 3. Connect the ignition instructions. 4. Brand of scope used 5. Describe the hooku 6. Start the engine and (vol Cylinder #1 Cylinder #2 Cylinder #3 Cylinder #4 Cylinder #5 | d: p procedure d observe the secondary Firing Voltage (KV) Itage should be 5-15 KV | ignition wa | aveform. Spark Line L | - ength (1 | |