

# Freeze Frame and MIL Activity

**Meets NATEF Task:** (A8-B-2) Diagnose the causes of emissions or driveability concerns with stored or active diagnostic trouble codes; obtain, graph, and interpret scan tool data. (P-1)

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

The purpose of this activity is to allow the service technician apply the use of freeze frames in the diagnosis of OBD II faults.

\_\_\_\_\_ 1. Connect a scan tool with the key on, engine off (KOEO), and disconnect the electrical connection from the throttle position (TP) sensor. Wait 3 seconds.

\_\_\_\_\_ 2. A TP sensor TP fault diagnostic trouble code (DTC) should have been set.

\_\_\_\_\_ Yes (DTC was set) \_\_\_\_\_ No (no DTC was set) Turn the ignition off and back on. Did the DTC set?  
\_\_\_\_\_ Yes \_\_\_\_\_ No

\_\_\_\_\_ 3. Using a scan tool, view the freeze frame created when the DTC was set.

\_\_\_\_\_ OK (freeze frame was set) \_\_\_\_\_ No (freeze frame was not set)

\_\_\_\_\_ 4. Is the malfunction indicator lamp (MIL or check engine) on? \_\_\_\_\_ Yes \_\_\_\_\_ No

\_\_\_\_\_ 5. Check service information and list the reason(s) that could cause the MIL to be on in the event of a disconnected TP sensor.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_ 6. Check service information and determine what needs to occur to turn off the MIL.

\_\_\_\_\_

\_\_\_\_\_

