

# U-Joint and CV Joint Service

**Meets NATEF Task:** (A3-D-3, A3-D-4, A3-D-5) Inspect, service, and replace shafts, shaft center support bearings yokes, boots, and CV joints; check shaft balance and phasing. (P-1, P-1, P-2)

Name \_\_\_\_\_ Date \_\_\_\_\_ Time on Task \_\_\_\_\_

Make/Model/Year \_\_\_\_\_ VIN \_\_\_\_\_ Evaluation: 4 3 2 1

\_\_\_\_\_ 1. Check service information and determine the specified procedures, tools, and torque specification needed to service CV joints.

Specified procedure: \_\_\_\_\_

\_\_\_\_\_

Tools/equipment: \_\_\_\_\_

\_\_\_\_\_

Torque specification: \_\_\_\_\_

\_\_\_\_\_ 2. Following the specified procedure, remove the drive axle shaft assembly.

Instructor's check \_\_\_\_\_



\_\_\_\_\_ 3. Following the specified installation procedure, check all that were replaced.

\_\_\_ Drive axle shaft assembly

\_\_\_ CV joint and boot

\_\_\_ CV joint boot only

\_\_\_ Other (specify) \_\_\_\_\_

\_\_\_\_\_ 4. Reinstall the drive axle shaft assembly.

Instructor's OK \_\_\_\_\_