Headlight Replacement and Aiming
Meets ASE Task: (A6-E-3) Inspect, replace, and aim headlights and bulbs.
(P-1)

Name	Date	Time on Task	
Make/Model/Year	VIN	Evaluation:	4 3 2 1
1. Check service inform replace and aim head	nation for the specified tools, lights.	equipment, and proced	ures to
	HORIZONTAL CENTE		DISTANCE BETWEEN HEADLAMPS  CENTER LINE OF SCREEN  ADJUSTABLE HORIZONTAL TAPES
		25 FEET (7.6 m) TED REFERENCE LINE HOP FLOOR	DIAGRAM OF LIGHT SCREEN
	VERTICAL CENTERLINE AHEAD OF LEFT HEADLAMP  HIGH INTENSITY AREA  ADJUSTING PATTERN FOR LOW	VERTICAL CENTERINE AHEAD OF RIGHT HEADLAMP HEIGHT OF LAMP CENTERS HIGH INTENSITY AREA  VERM ADJUSTING	VEHICLE AXIS  VERTICAL CENTERLINE AHEAD OF RIGH HEADLAMP HEIGHT OF LAMP CENTERS  PATTERN FOR HIGH BEAM
2. What type of headlight	hts are used on the vehicle?	ADDOTING	TATIENTOTTIONSEAM
High-intens	m placement bulbs sity discharge (HID) cribe)		
3. Is alignment equipme	ent needed?Yes!	No	
If yes, describe:			
	equipped with a bubble level		