
Name				

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

 The maximum traction between a tire and the road occurs when the tire is A) locked and skidding B) rotating freely 	1)
C) slipping 15% to 25% D) slipping 80% to 90%	
2) Which of the following is NOT a function of an antilock brake system (ABS)?	2)
A) Helps maintain vehicle control while braking	
B) Allows drivers to drive more closely to the vehicle in front	
C) Maintain directional stability on slippery surfaces	
D) Allow elimination of the proportioning valve	
3) Technician A says that some ABS wheel speed sensors are used as part of the tire pressure	3)
monitoring system (TPMS). Technician B says that the ABS is used as part of the hill assist	
system. Which technician is correct?	
A) Technician A only	
B) Technician B only	
C) Both technicians	
D) Neither technician	
4) Technician A says that most ABS units are non-integral. Technician B says that some ABS wheel speed sensors do not produce a useable signal below about 2 mph (3 km/h). Which technician is	4)
correct?	
A) Technician A only	
B) Technician B only	
C) Both technicians	
D) Neither technician	
5) Which of the following components is common to all vehicles equipped with ABS?	5)
A) Pedal travel sensor	
B) Combination valve assembly	
C) Pressure relief valves	
D) Hydraulic control unit	
6) Technician A says digital wheel speed sensors produce a variable frequency AC voltage.	6)
Technician B says digital wheel speed sensors use a DC reference voltage supply and produce a	0)
square wave signal. Which technician is correct?	
A) Technician A only	
B) Technician B only	
C) Both technicians	
D) Neither technician	

7) Which of these is NOT an additional function of the ABS module?

- A) Hill start assist
- B) Automatic braking
- C) Electric steering assist
- D) Electronic proportioning
- 8) Which of these is a 3 channel antilock brake system?



- 9) A technician is trying to identify which type of antilock system is installed on a vehicle. A speed
 9) ______
 sensor is attached to the rear differential housing. Which type of system could this be?
 - A) Five-channel ABS
 - B) Four-channel ABS
 - C) Three-channel ABS
 - D) Two-channel ABS
- 10) Technician A says an antilock system that operates on the select-low principle will control each rear wheel individually. Technician B says systems using the select-low principle regulates rear wheel brake pressure to both rear wheel simultaneously. Which technician is correct?
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician

8)

7) _____

10) _____

Answer Key Testname: AT6_110B

1) C Page Ref: 1307 2) B Page Ref: 1306, 1315 3) C Page Ref: 1315 4) C Page Ref: 1310-1311 5) D Page Ref: 1310 6) B Page Ref: 1312 7) A Page Ref: 1315 8) B Page Ref: 1309 9) C Page Ref: 1309

10) B

Page Ref: 1309