D) Neither A nor B

<ul> <li>(a) Toe</li> <li>(b) Camber</li> <li>(c) Caster</li> <li>(d) SAI</li> </ul> (e) Included angle is <ul> <li>(e) A) SAI + caster</li> <li>(e) Camber + Caster</li> <li>(e) Camber + SAI</li> <li>(e) D) toe + camber</li> </ul> (f) Many manufacturers specify some degree of toe. <ul> <li>(e) A) positive</li> <li>(f) B) negative</li> </ul>	2)
B) Camber C) Caster D) SAI  Included angle is A) SAI + caster B) camber + caster C) camber + SAI D) toe + camber  Many manufacturers specify some degree of toe. A) positive B) negative	
D) SAI  Included angle is  A) SAI + caster  B) camber + caster  C) camber + SAI  D) toe + camber  Many manufacturers specify some degree of toe.  A) positive  B) negative	
) Included angle is  A) SAI + caster  B) camber + caster  C) camber + SAI  D) toe + camber  ) Many manufacturers specify some degree of toe.  A) positive  B) negative	
A) SAI + caster B) camber + caster C) camber + SAI D) toe + camber  Many manufacturers specify some degree of toe. A) positive B) negative	
B) camber + caster C) camber + SAI D) toe + camber  Many manufacturers specify some degree of toe. A) positive B) negative	
C) camber + SAI D) toe + camber  ) Many manufacturers specify some degree of toe. A) positive B) negative	
D) toe + camber  ) Many manufacturers specify some degree of toe. A) positive B) negative	
Many manufacturers specify some degree of toe.  A) positive B) negative	- •
A) positive B) negative	- \$
B) negative	3)
C) zero	
D) none of these	
) What alignment angle is shown in this drawing?	4)
A) Thrust angle	
B) Total toe	
C) Center line	
D) Rear camber	
) Positive camber means	5)
A) the top of the tire is tilted outward	,
B) the top of the tire is tilted inward	
C) the front of the tire is pointed inward	
D) the front of the tire is pointed rearward	
) Which statement(s) is/are TRUE about included angle?	6)

7) Excessive toe-in will cause tire wear	7)
A) on the outside shoulder of the tire	
B) on the inside shoulder of the tire	
C) in the middle of the tire	
D) on both tire edges	
8) If the turning radius (toe out on turns, or TOOT) is out of specification, what part or component	8)
is defective?	
A) The strut is bent.	
B) The steering arm is bent.	
C) The spindle is bent.	
D) The control arm is bent.	
9) If caster is adjustable for a given vehicle, how does the technician adjust it?	9)
A) Changing the length of the strut rod	
B) Adding or removing shims	
C) Turning an eccentric cam	
D) All of these are ways to adjust caster.	
10) Which alignment angle is adjustable on all vehicles?	10)
A) Camber	
B) Caster	
C) Toe	
D) SAI	

## Answer Key

Testname: AT6\_124B

- 1) A
  - Page Ref: 1529
- 2) C
- Page Ref: 1531
- 3) A
  - Page Ref: 1530
- 4) A
  - Page Ref: 1535
- 5) A
- Page Ref: 1524
- 6) C
- Page Ref: 1531
- 7) A
  - Page Ref: 1530
- 8) B
  - Page Ref: 1534
- 9) D
  - Page Ref: 1528
- 10) C
  - Page Ref: 1530