NT			
Name			

1) Technician A says that carbon fiber driveshafts need support bearings every 24 inches.	1)
Technician B says that carbon fiber and aluminum driveshafts reduce rotating mass and are	e
more efficient than steel driveshafts. Which technician is correct?	
A) Technician A only	
B) Technician B only	
C) Both technicians	
D) Neither technician	
2) Which of the following is an acceptable working angle for a RWD driveshaft?	2)
A) 6 degrees	
B) 0 degrees	
C) 1 degree	
D) None of these are correct.	
3) Small differences in driveshaft U-joint angles cause vibration	3)
A) when accelerating from a stop	
B) at highway speeds	
C) both A and B	
D) neither A nor B	
4) Drive axle shafts are also called	4)
A) double-Cardan shafts	
B) half shafts	
C) driveshafts	
D) propeller shafts	
5) Which series U-joint has the greatest torque capacity?	5)
A) 1260	
B) 1310	
C) 1350	
D) 1480	
6) A dent in a prop shaft can cause damage that may result in failure when engine torque is	6)
applied.	
A) True	
B) False	
7) A CV joint can operate at an angle of up to 40 degrees.	7)
A) True	
B) False	

9) Technician A says only 4WD rear driveshafts are balanced. Technician B says all RWD driveshafts are balanced. Which technician is correct?	9)
A) Technician A only	
B) Technician B only	
C) Both technicians	
D) Neither technician	
10) Technician A says that two U-joints are used on a driveshaft to prevent vibration. Technician B says that the more equal the U-joint angles, the less chance of driveshaft vibration. Which technician is correct?A) Technician A onlyB) Technician B only	10)

- C) Both technicians
 D) Neither technician

Answer Key

Testname: AT6_128B

1) B

Page Ref: 1605

2) C

Page Ref: 1607

3) A

Page Ref: 1606

4) B

Page Ref: 1610

5) D

Page Ref: 1609

6) A

Page Ref: 1606

7) A

Page Ref: 1609

8) A

Page Ref: 1608

9) B

Page Ref: 1605

10) C

Page Ref: 1606