

Name _____

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

- 1) Fixed brake drums are held on by a spindle nut. 1) _____
A) True
B) False

- 2) Technician A says bolts are used to attach the wheel cylinder to the backing plate. Technician B says clips are used to attach the wheel cylinder to the backing plate. Which technician is correct? 2) _____
A) Technician A only
B) Technician B only
C) Both technicians
D) Neither technician

- 3) A squeaking sound is heard from the rear drum brakes as the brake pedal is applied and released. Which of these could be the cause? 3) _____
A) A bent brake shoe
B) Hard spots on the brake drum
C) Dry brake shoe support pads
D) Shoes out of adjustment

- 4) The use of special tools is not important when removing return springs. 4) _____
A) True
B) False

- 5) Technician A says to use masking tape temporarily over the lining material to help prevent getting grease on the lining. Technician B says that grease on the brake lining can cause the brakes to grab. Which technician is correct? 5) _____
A) Technician A only
B) Technician B only
C) Both technicians
D) Neither technician

- 6) Wheel cylinders are being discussed. Technician A says that if a wheel cylinder is not leaking fluid it is OK. Technician B says that wheel cylinders requires further inspection. Which technician is correct? 6) _____
A) Technician A only
B) Technician B only
C) Both technicians
D) Neither technician

- 7) Technician A says that the tinnerman nuts used to hold the brake drum on should be reinstalled when the drum is replaced. Technician B says that a drum should be removed inside a sealed vacuum enclosure or washed with water or solvent to prevent possible asbestos dust from being released into the air. Which technician is correct? 7) _____
- A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician
- 8) When brake linings are replaced, the _____ should also be inspected. 8) _____
- A) Camber angle of the suspension
 - B) Condition of the wheel cylinders
 - C) Both A and B
 - D) Neither A nor B
- 9) Technician A says that the backing plate should be lubricated with chassis grease on the shoe pads. Technician B says that the brakes will squeak when applied if the shoe pads are not lubricated. Which technician is correct? 9) _____
- A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician
- 10) Technician A says that a cracked brake lining is OK as long as the thickness is more than 0.060 inch. Technician B says that weak hold-down springs can cause brake noise. Which technician is correct? 10) _____
- A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician

Answer Key

Testname: BRAKES7_11A

- 1) A
Page Ref: 176
- 2) C
Page Ref: 182
- 3) C
Page Ref: 186-187
- 4) B
Page Ref: 179
- 5) C
Page Ref: 185
- 6) B
Page Ref: 181
- 7) B
Page Ref: 176, 178
- 8) B
Page Ref: 181
- 9) B
Page Ref: 179
- 10) B
Page Ref: 180