

Name _____

SHORT ANSWER. Write the word or phrase that best completes each statement or answers the question.

1) What is the difference between a dual-servo and a leading-trailing drum brake system?

2) What is a labyrinth seal?

3) List all the parts of a typical drum brake.

4) Why should a driver allow the brakes to cool before backing a long distance?

5) How does a self-adjusting brake mechanism work?

Answer Key

Testname: BRAKES7_SHORT10

- 1) A dual-servo brake uses the force of the primary brake shoe to engage the secondary shoe against the drum with even greater force. In a leading/trailing drum brake, each shoe works independently resulting in a more linear brake application.
Page Ref: 165-166
- 2) The lip fits into a machined groove in the open edge of the brake drum to provide an even better water barrier or seal. This type of seal is called a labyrinth seal.
Page Ref: 159
- 3) The parts of a typical drum brake include, backing plate, anchor pin, primary (leading) shoe, secondary (trailing) shoe, hold-down springs, adjusting levers, and return springs.
Page Ref: 163
- 4) Self-adjusters can over adjust the rear drum brakes if the brake drums are hot and have increased in diameter due to the heat.
Page Ref: 171
- 5) A typical self-adjuster moves the star wheel adjuster when the brakes are released after a brake application when the vehicle is traveling in reverse.
Page Ref: 169-170