

Name \_\_\_\_\_

**SHORT ANSWER. Write the word or phrase that best completes each statement or answers the question.**

1) Where are the fuel filters located in the fuel system?

---

---

---

2) What three methods can be used to test a fuel pump?

---

---

---

3) What are the three most commonly used pump designs?

---

---

---

4) What is the proper way to disconnect and connect plastic fuel line connections?

---

---

---

5) What accident and rollover devices are installed in a fuel delivery system?

---

---

---

## Answer Key

Testname: AEEP8\_SHORT36

- 1) Fuel filters are located between the fuel pump and the injectors. Often, the fuel filter is placed inside the fuel pump module assembly, which is replaced as a unit.  
Page Ref: 567
- 2) The three methods that can be used to check a fuel pump include: pressure testing, volume testing, and current draw.  
Page Ref: 568-572
- 3) The three most used fuel pump designs include the roller cell or vane pump, the rotary vane pump, and a gerotor.  
Page Ref: 563
- 4) The proper way to disconnect plastic fuel lines is to use a release tool to unlock the retainer, and use a drop of oil to help lubricate the seal when the ends are reattached.  
Page Ref: 560-561
- 5) Accident and rollover devices include check valves or an inertia switch.  
Page Ref: 560; 564-565