

Name \_\_\_\_\_

**MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.**

- 1) The typical RWD driveshaft rotates about \_\_\_\_\_ times faster than the wheels.
  - A) three
  - B) two
  - C) five
  - D) seven
- 2) The most common complaint from CV joint failure is noise while turning.
  - A) True
  - B) False
- 3) What is recommended to install the drive axle shaft to avoid damage to the hub bearing?
  - A) Torque wrench
  - B) Cordless impact wrench
  - C) Pickle fork
  - D) Hub bearing puller
- 4) Two technicians are discussing FWD driveshaft service. Technician A says that removal of the driveshaft usually requires partial disassembly of the front suspension. Technician B says that the first step in driveshaft removal is to loosen the front hub nut. Which technician is correct?
  - A) Technician A only
  - B) Technician B only
  - C) Both technicians A and B
  - D) Neither technician A nor B
- 5) What could be a symptom of a defective U-joint?
  - A) A vibration at highway speed
  - B) A clicking sound
  - C) A clunking sound
  - D) Any of the above
- 6) Which tool is used to measure U-joint working angles?
  - A) Micrometer
  - B) Dial indicator
  - C) Vernier caliper
  - D) None of these are correct.
- 7) When servicing a driveshaft, technician A says that its a good idea to tape the U-joint caps to prevent them from coming off. Technician B says that needle bearings are used with this type of U-joints. Which technician is correct?
  - A) Technician A only
  - B) Technician B only
  - C) Both technicians A and B
  - D) Neither technician A nor B

- 8) A defective (collapsed) engine mount on a front-wheel drive vehicle can cause a vibration.
- A) True
  - B) False
- 9) Technician A says that the outer portion of the driveshaft can be used as a slide hammer to pop the inboard CV joint out of the transaxle. Technician B says that you should not hammer on the outer end of the outboard CV joint to get it out of the hub. Which technician is correct?
- A) Technician A only
  - B) Technician B only
  - C) Both technicians A and B
  - D) Neither technician A nor B
- 10) The last step after installing a replacement CV boot is to \_\_\_\_\_.
- A) "Burp" the boot
  - B) lubricate the CV joint with chassis grease
  - C) mark the location of the boot on the drive axle shaft
  - D) separate the CV joint before installation

## Answer Key

Testname: ASSA8\_18B

- 1) A  
Page Ref: 310
- 2) A  
Page Ref: 316
- 3) A  
Page Ref: 317
- 4) C  
Page Ref: 316-317
- 5) D  
Page Ref: 310
- 6) D  
Page Ref: 315
- 7) C  
Page Ref: 313
- 8) A  
Page Ref: 320
- 9) B  
Page Ref: 318
- 10) A  
Page Ref: 317