SHORT ANSWER. Write the word or phrase that best completes each statement or answers the question.  1) What is the purpose of a track rod?  2) What is meant by "dog tracking"?  3) What must be done to ensure safety when replacing the rear shock absorbers?  4) What are the disadvantages of a solid rear axle?  5) What is the purpose of a torque arm?	utomotive Steering, Suspension, and Alignment, 8th Edition hapter 9
1) What is the purpose of a track rod?  2) What is meant by "dog tracking"?  3) What must be done to ensure safety when replacing the rear shock absorbers?  4) What are the disadvantages of a solid rear axle?	ame
2) What is meant by "dog tracking"?  3) What must be done to ensure safety when replacing the rear shock absorbers?  4) What are the disadvantages of a solid rear axle?	HORT ANSWER. Write the word or phrase that best completes each statement or answers the question.
3) What must be done to ensure safety when replacing the rear shock absorbers?  4) What are the disadvantages of a solid rear axle?	1) What is the purpose of a track rod?
3) What must be done to ensure safety when replacing the rear shock absorbers?  4) What are the disadvantages of a solid rear axle?	
4) What are the disadvantages of a solid rear axle?	2) What is meant by "dog tracking"?
4) What are the disadvantages of a solid rear axle?	
4) What are the disadvantages of a solid rear axle?	3) What must be done to ensure safety when replacing the rear shock absorbers?
5) What is the purpose of a torque arm?	4) What are the disadvantages of a solid rear axle?
5) What is the purpose of a torque arm?	
	5) What is the purpose of a torque arm?

## Answer Key

Testname: ASSA8\_SHORT9

- 1) A track rod is a rod attached to the body or frame on one end and the rear axle on the other. The purpose of the track rod is to keep the rear axle centered under the vehicle. The suspension may use either coil springs or struts. Page Ref: 174
- 2) Dog tracking refers to the sideways angle of the vehicle while traveling straight. It is commonly caused by the rear axle steering the vehicle toward one side, while the driver controls the direction of the vehicle with the front wheels.

Page Ref: 180

3) When replacing rear shock absorbers, the rear axle must be supported by tall safety standards to prevent the rear axle from dropping when the shocks are removed.

Page Ref: 177

4) Solid rear axles have the following disadvantages: high unsprung weight, side-to-side shock transference, and reduced tire adhesion.

Page Ref: 172

5) A torque arm absorbs engine torque and reduces axle windup.

Page Ref: 173