

Name _____

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

- 1) Technician A says to use synthetic grease to lubricate the backing plate. Technician B says to use special lithium-based brake grease to lubricate the backing plate. Which technician is correct? 1) _____
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians A and B
 - D) Neither technician A nor B

- 2) Technician A says that many vehicle manufacturers recommend that wheel cylinders not be honed because of the special surface finish inside the bore. Technician B says that some experts recommend that the wheel cylinders be replaced every time the brake linings are replaced. Which technician is correct? 2) _____
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians A and B
 - D) Neither technician A nor B

- 3) Technician A says that when repairing brakes, it is a good practice to inspect the backing plate for a bent or cracked structure. Technician B says that the pads of the backing plate should be lubricated with heavy grease before installing new shoes. Which technician is correct? 3) _____
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians A and B
 - D) Neither technician A nor B

- 4) Technician A says that bolts are used to attach the wheel cylinder to the backing plate. Technician B says that clips are used to attach the wheel cylinder to the backing plate. Which technician is correct? 4) _____
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians A and B
 - D) Neither technician A nor B

- 5) Old brake shoes are often returned to the manufacturer when new friction material is installed. These old shoes are usually called the _____. 5) _____
 - A) core
 - B) return
 - C) deposit
 - D) root

- 6) Today, most wheel cylinders are rebuilt, rather than replaced. 6) _____
 - A) True
 - B) False

7) Most manufacturers recommend that brake parts should be cleaned with _____. 7) _____
A) clean water only
B) denatured alcohol
C) stoddard solvent
D) detergent and water

8) Technician A says that starwheel adjusters use different threads (left- and right-handed) for the left and right sides of the vehicle. Technician B says that the threads and end caps of the adjusters should be lubricated with brake grease before being installed. Which technician is correct? 8) _____
A) Technician A only
B) Technician B only
C) Both technicians A and B
D) Neither technician A nor B

9) This tool is used to remove the _____. 9) _____



- A) master cylinder snap ring
- B) brake shoe hold down clip
- C) wheel cylinder snap ring
- D) parking brake lever snap ring

10) When manually loosening brakes equipped with automatic adjusters, the _____ must be pushed or held out of the way. 10) _____
A) adjuster lever
B) starwheel adjuster
C) return spring
D) adjuster cable

Answer Key

Testname: CHASSIS8_12A

1) C

Page Ref: 168, 173

2) C

Page Ref: 170

3) A

Page Ref: 168

4) C

Page Ref: 171

5) A

Page Ref: 172

6) B

Page Ref: 170

7) B

Page Ref: 172

8) C

Page Ref: 172

9) C

Page Ref: 171

10) A

Page Ref: 167