

Name \_\_\_\_\_

**MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.**

- 1) Technician A says that a hoist can be stopped at any level as long as the safety latch engages. Technician B says that the vehicle should be hoisted to the top of the hoist travel for safety. Which technician is correct? 1) \_\_\_\_\_  
A) Technician A only  
B) Technician B only  
C) Both technicians A and B  
D) Neither technician A nor B
- 2) Technician A says that tall safety stands can be used to provide additional support for a vehicle while on a hoist. Technician B says that some newer vehicles have a decal indicating the recommended hoisting lift points. Who is right? 2) \_\_\_\_\_  
A) A only  
B) B only  
C) Both A and B  
D) Neither A nor B
- 3) A safety stand is also called a \_\_\_\_\_. 3) \_\_\_\_\_  
A) Jack  
B) Jack stand  
C) Bottle jack  
D) Safety stool
- 4) The SAE standard for hoist location is \_\_\_\_\_. 4) \_\_\_\_\_  
A) J-1980  
B) SAE-2009  
C) JRP-2184  
D) J-14302
- 5) When checking stability, how high should the vehicle be raised? 5) \_\_\_\_\_  
A) About 2 inches (5 cm)  
B) About 6 inches (15 cm)  
C) About 1 foot (30 cm)  
D) About 3 feet (91 cm)
- 6) Technician A says that a creeper should be stored vertically. Technician B says that a creeper should be stored on its casters. Which technician is correct? 6) \_\_\_\_\_  
A) Technician A only  
B) Technician B only  
C) Both technicians A and B  
D) Neither technician A nor B

- 7) What can be used to prevent damage to vehicle components when hoisting? 7) \_\_\_\_\_
- A) A block of wood used with jack stands
  - B) The correct size lift pads
  - C) Both A and B
  - D) Neither A nor B
- 8) Which of these is LEAST likely to be used to lift a vehicle in a professional shop? 8) \_\_\_\_\_
- A) Drive-up ramps
  - B) Floor jacks
  - C) Two post frame engaging hoist
  - D) None of these
- 9) Tall safety stands would be used to \_\_\_\_\_. 9) \_\_\_\_\_
- A) Help support the vehicle when a major component is removed from the vehicle
  - B) Lift a vehicle
  - C) Lift a component such as an engine high off the ground
  - D) Both B and C
- 10) Technician A says to never look away from a vehicle being hoisted. Technician B says that the vehicle must be raised off the mechanical locks before lowering. Which technician is correct? 10) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians A and B
  - D) Neither technician A nor B

## Answer Key

Testname: INTRO\_18A

- 1) A  
Page Ref: 176
- 2) C  
Page Ref: 174
- 3) B  
Page Ref: 173
- 4) C  
Page Ref: 174
- 5) C  
Page Ref: 175
- 6) A  
Page Ref: 173
- 7) B  
Page Ref: 175
- 8) A  
Page Ref: 176
- 9) A  
Page Ref: 174
- 10) C  
Page Ref: 175-176