2022 ASE Correlation Chart

Light Vehicle Diesel Engines (A9)

A. GE	NERAL DIAGNOSIS	Text	Task
		Page #	Page #
1.	Verify the complaint, and road/dyno test vehicle; review	68; 241	28
	driver/customer concerns/ expectations and vehicle service		
	history (if available); determine further diagnosis.		
2.	Record vehicle identification number (VIN). Identify	68-69;	1, 85,
	engine model, calibration and serial numbers to research	250-	86, 87,
	applicable vehicle and service information, service	252;	88
	precautions, and technical service bulletins; determine	268-	
	needed actions.	272;	
		290-	
		292;	
		309-	
		312	
3.	Perform scan tool check and visual inspection for physical	240-	81
	damage and missing, modified, or tampered components;	245	
	determine needed actions.		
4.	Check and record electronic diagnostic codes, freeze frame	242-	82
	and/or operational data; monitor scan tool data; determine	245	
	further diagnosis.		
5.	Clear diagnostic trouble codes (DTCs) and verify the	68-69;	83
	repair.	242-	
		246	
6.	Inspect engine assembly and compartment for fuel, oil,	69-72;	29
	coolant, exhaust, or other leaks; determine needed repairs.	240-	
		242	
7.	Inspect engine compartment wiring harness, connectors,	68-69	76
	seals, and locks; check for proper routing and condition;		
	determine needed repairs.		
8.	Listen for and isolate engine noises; determine needed	71-72	30
	repairs.		
9.	Isolate and diagnose engine related vibration problems;	71-72	31
	determine needed actions.		
10	. Check engine exhaust for abnormal odor and/or smoke	240-	32
	color and volume; determine further diagnosis.	242	
11	. Check fuel for contamination, quantity, quality, and	130-	59,60
	consumption; determine needed actions.	131	
12	. Perform crankcase pressure test; determine further	72-73	2, 33,
	diagnosis.		58
13	. Diagnose surging, rough operation, misfiring, low power,	74-77	34
-	slow deceleration, slow acceleration, and shutdown		
	problems; determine needed actions.		
1.4	. Check cooling system for freeze point, level,	70-71	20, 22,
14			, ,
14	contamination, condition, temperature, pressure,		26, 27

A. GENERAL DIAGNOSIS	Text	Task
	Page #	Page #
15. Check lubrication system for contamination, oil level, temperature, pressure, filtration, and oil consumption; take oil sample and obtain oil analysis if needed; determine needed repairs.	70-74	35
16. Diagnose no-cranking, cranks but fails to start, hard starting, and starts but does not continue to run problems; determine needed actions.	77-80	36
17. Diagnose engine problems caused by battery condition, connections, or excessive key-off battery drain; determine needed repairs.	77-79	37
 Diagnose engine problems resulting from an electrical undercharge, overcharge, or a no-charge condition; determine needed action. 	77-79	38
B. CYLINDER HEAD AND VALVE TRAIN DIAGNOSIS	Text	Task
AND REPAIR	Page #	Page #
1. Remove, inspect, disassemble, and clean cylinder head assembly(s).	84-89	39
2. Inspect threaded holes, studs, and bolts for serviceability; service/replace as needed.	94	40
 Measure cylinder head thickness, and check mating surfaces for flatness, corrosion, warpage and surface finish; inspect for cracks/damage; check condition of passages; inspect core and gallery plugs; determine serviceability and needed repairs. 	90-91	41
 Inspect valves, guides, seats, springs, retainers, rotators, locks and seals; determine serviceability and needed repairs. 	28-30	42
 Inspect and/or replace injector sleeves, glow plug sleeves, and seals; pressure test to verify repair (if applicable); measure injector tip, nozzle, or prechamber protrusion where specified by manufacturer. 	36	43
6. Inspect, and/or replace valve bridges (crossheads) and guides; adjust bridges (crossheads) if applicable.	33-35; 104	12
 Reassemble, check, and determine required cylinder head gasket thickness; install cylinder head assembly and gasket as specified by the manufacturer. 	103	45
 Inspect pushrods, rocker arms, rocker arm shafts, electronic components, wiring harness, seals; repair/replace as needed. 	305	13

	LINDER HEAD AND VALVE TRAIN DIAGNOSIS	Text	Task
AND I	REPAIR	Page #	Page #
9.	Inspect, install, and adjust cam followers, lash adjusters and retainers; adjust valve clearance if applicable.	33; 104	44
10.	Inspect, measure, and replace/reinstall overhead camshaft	31-32;	14
	and bearings; measure and adjust endplay.	312;	
		320	
11.	Inspect and time drive gear train components (includes	103	15
	gear, chain, and belt systems).		
EN	GINE BLOCK DIAGNOSIS AND REPAIR	Text	Task
		Page #	Page #
1.	Remove, inspect, service, and install pans, covers,	83-84	2
	ventilation systems, gaskets, seals, and wear rings.		
2.	Disassemble, clean and inspect engine block for cracks;	84-85;	3
	check mating surfaces and related components for damage	90-91	
	or warpage and surface finish; check deck height; check		
	condition of passages, core, and gallery plugs; inspect		
	threaded holes, studs, dowel pins and bolts for		
	serviceability; service/replace as needed.		
3.	Inspect and measure cylinder walls for wear and damage;	98-100	4
	determine needed service.		
4.	Inspect in-block camshaft bearings for wear and damage;	23-24	5
	replace as needed.		
5.	Inspect, measure, and replace/reinstall in-block camshaft;	23-24;	6
	measure and correct end play; inspect, replace/reinstall,	31-33	
	and adjust cam followers (if applicable).		
6.	1 5	18-19	7
	finish, cracks, and damage; check condition of oil		
	passages; check passage plugs; measure journal diameters;		
	check mounting surfaces; determine needed service.		
7.	Determine the proper select-fit components such as	98-100	8
	pistons, connecting rod and main bearings.		
8.	Inspect and replace main bearings; check cap fit and	95-96	9
	bearing clearances; check and correct crankshaft end play.		
9.	Inspect, replace, verify, and adjust the drive gear train	103-	10
	components (includes gear, chain, and belt systems).	104	
	Inspect, measure, or replace pistons, pins, and retainers.	98-100	11, 48
	Measure piston-to-cylinder wall clearance.	98-100	46
12.	Identify piston, connecting rod bearing, and main bearing	19-23	47
	wear patterns that indicate connecting rod and crankshaft		
	alignment or bearing bore problems; check bearing bore		
	and bushing condition; determine needed repairs.		

C. ENGINE BLOCK DIAGNOSIS AND REPAIR	Text	Task
	Page #	Page #
13. Check ring-to-groove fit and end gaps; install rings on	98-100	48
pistons; assemble pistons and connecting rods and insta	.11	
in block; check piston height/protrusion; check liner		
height/protrusion (if applicable); replace rod bearings a		
check clearances; check condition, position, and clearan	nce	
of piston cooling jets (nozzles).		
14. Inspect crankshaft vibration damper; determine needed	18	49
repairs.		
15. Inspect flywheel/flexplate and/or dual-mass flywheel	18-19	50
(including ring gear) and mounting surfaces for cracks,		
wear, and runout; determine needed repairs.		
D. LUBRICATION AND COOLING SYSTEMS DIAGNO		Task
ND REPAIR	Page #	Page #
1. Verify base engine oil pressure and check operation of	73-74	16
pressure sensor/switch and pressure gauge; verify engin		
oil temperature and check operation of temperature sen	sor.	
2. Inspect, measure, repair/replace oil pump, housing, driv	ves, 43	17
pipes, and screens; check drive gear clearance.		
3. Inspect, repair/replace oil pressure regulator assembly	40-43	18
including: housing, bore, spring, regulator valve(s), oil		
filter by-pass valve(s), and anti-drain back valve.		
4. Inspect, clean, test, and reinstall/replace oil cooler, by-	bass 43-46	19
valve, lines, and hoses.		
5. Inspect turbocharger lubrication and cooling systems;	110;	51
repair/replace as needed.	115	51
 Change engine oil and filters using proper type, viscosi 		75
and rating per manufacturer specifications.	iy, 170	15
	ve 57	21
7. Inspect and reinstall/replace pulleys, tensioners, and dribelts; adjust drive belts and check alignment.	ve 37	21
· · · · · · · · · · · · · · · · · · ·	frame 52.54	
8. Verify coolant temperature; check operation of tempera	ture 53-54	22
and level sensors, switches, and temperature gauge.		
9. Inspect and replace thermostat(s), by-pass(es), housing	(s), 52-54	23
and seal(s).		
10. Flush and refill cooling system; following manufacture	r's 66	24
specification, add proper coolant type; bleed air from		
system.		
11. Inspect and replace water pump(s), housing(s), hoses, a	nd 57-58	25
idler pulley(s) or drive gear.		
12. Inspect radiator(s), pressure cap(s), and tank(s); pressure	e 59-60	26
test cooling system and radiator cap(s); determine need		
repairs.		
•	ch, 58-59	27
13. Inspect and repair/replace cooling fan, fan hub, fan clut		

E. AIF	R INDUCTION AND EXHAUST SYSTEMS	Text	Task
DIAG	NOSIS AND REPAIR	Page #	Page #
1.	Inspect and service/replace air induction piping, air	117-	53
	cleaner, and element; determine needed actions.	121	
2.	Perform intake manifold pressure tests; inspect, test, clean,	119	54
	and/or replace charge air cooler and piping system;		
	determine needed actions.		
3.	Inspect, test, and replace turbocharger(s) (including	111-	52
	variable ratio/geometry VGT), pneumatic, hydraulic,	112	
	vacuum, and electronic controls and actuators; inspect, test,		
	and replace wastegate and wastegate controls.		
4.	Inspect, test, and replace intake manifold(s), variable	119-	55
	intake manifold(s), gaskets, actuators, temperature and	120	
	pressure sensors, and connections.		
5.	Perform exhaust back pressure and temperature tests;	115	71
	determine needed actions.		
6.	Inspect and repair/replace exhaust manifold(s), gaskets,	124-	72
	piping, mufflers, and mounting hardware.	125	
7.	Inspect, test, and repair/replace preheater/inlet air heater	121-	56
	and/or glow plug system and controls.	124	
8.	Inspect, test, and replace exhaust aftertreatment system	167-	73
	components and controls, including diesel oxidation	173	
	catalyst (DOC), selective catalyst reduction (SCR), diesel		
	exhaust fluid (DEF), diesel particulate filter (DPF); check		
	regeneration system operation.		
9.	Inspect, test, service, and replace EGR system components	121-	74
	including EGR valve(s), EGR cooler by-pass valve(s),	127	
	EGR cooler(s), piping, electronic sensors, actuators,		
	controls, and wiring.		
10.	Inspect, test, and replace airflow control (throttle) valve(s)	124-	57
	and controls.	125	
11.	Inspect, test, and replace crankcase ventilation system	72-73	58
	components, including sensors, filters, valves, and piping.		
F. FUI	EL SYSTEM DIAGNOSIS AND REPAIR	Text	Task
		Page #	Page #
1.	Inspect, clean, test, and repair/replace fuel system tanks,	135-	61
	vents, caps, mounts, valves, single/dual supply and return	137	
	lines, and fittings.		
2.	Inspect, clean, test, and repair/replace fuel transfer and/or	137-	62
	supply pump, sensors, strainers, fuel/water	138	
	separators/indicators, filters, heaters, coolers, ECM cooling		
	plates (if applicable), and mounting hardware.		
3.	Check fuel system for air; determine needed repairs; prime	137;	63
	and bleed fuel system; check and repair/replace primer	279	
	pump.		
4.	Inspect, test, and repair/replace low fuel pressure regulator	140	64
	supply and return systems, including low pressure		
	switches.		

F. FUEL SYSTEM DIAGNOSIS AND REPAIR	Text	Task
	Page #	Page #
5. Inspect and reinstall/replace high-pressure injection lines,	144-	65
fittings, transfer tubes, seals, and mounting hardware.	146	
6. Inspect, adjust, and repair/replace electronic throttle and	284	66
PTO control devices, circuits, and sensors.		
7. Perform on-engine inspections, tests, and replace high	151-	67
pressure common rail fuel system components and	154	
electronic controls.		
8. Perform on-engine inspections and tests; replace hydraulic	158-	70
electronic unit injector(s) (HEUI) components and	163	
electronic controls.		
9. Perform on-engine inspections and tests; replace pump-	154-	68
line-nozzle fuel system (PLN-E) components and	155	
electronic controls.		
10. Perform on-engine inspections and tests; replace electronic	153-	69
unit injector(s) (EUI) components and electronic controls.	154	
11. Inspect and replace electrical connector terminals, pins,	151	77
harnesses, seals, and locks.		
12. Connect diagnostic scan tool to vehicle/engine; access,	243-	84
verify and update software calibration settings, injector	246	
calibration codes; perform control module re-learn		
procedures as needed.		
13. Use a diagnostic scan tool to inspect and test electronic	230-	80
engine control system, sensors, actuators, electronic	236	
control modules, and circuits; determine further diagnosis.		
14. Measure and interpret voltage, voltage drop, amperage, and	188-	78
resistance readings using a digital multimeter (DMM) or	195	
appropriate test equipment.		
15. Diagnose engine problems resulting from failures of	230-	79
interrelated systems (for example: cruise control, security	236	
alarms/theft deterrent, transmission controls, exhaust		
aftertreatment systems, electronic stability control, or non-		
OEM installed accessories).		