

Automotive Engines 10th

Chapter 34 Engine Assembly

MATCHING. Choose the item in column 2 that best matches each item in column 1.

- | | | |
|---------------------------------------|--------------------------|-----------|
| 1. Assembly preparation step | A. TTY bolts | 1. _____ |
| 2. Head bolt sequence | B. Undersized | 2. _____ |
| 3. Cleans bolt holes | C. From center to ends | 3. _____ |
| 4. Bolt requires replacement | D. From left to right | 4. _____ |
| 5. Cause of bearing failure | E. Thread chaser | 5. _____ |
| 6. Used to install pistons | F. Clean gasket surfaces | 6. _____ |
| 7. Bearings for a reground crankshaft | G. Dial indicator | 7. _____ |
| 8. Checks ring gap | H. Dirt | 8. _____ |
| 9. Checks bearing clearance | I. Oversized | 9. _____ |
| 10. Checks crankshaft endplay | J. Ring compressor | 10. _____ |
| | K. Feeler gauge | |
| | L. Pan bolts | |
| | M. Plastigage | |

Answer Key

Testname: ENGINES 10 MATCH 34

1. F
Page Ref: 484
2. C
Page Ref: 498
3. E
Page Ref: 485
4. A
Page Ref: 500
5. H
Page Ref: 489
6. J
Page Ref: 495
7. B
Page Ref: 490
8. K
Page Ref: 494
9. M
Page Ref: 490
10. G
Page Ref: 492