


Pistons, Rings, And Connecting Rods

Chapter 29



<http://jameshalderman.com>

ACROSS

- 1 If an engine is designed not to have the pistons hitting the valves, if the timing belt or chain breaks, the engine is called _____.
- 4 A ring gap that is too great will allow excessive _____.
- 7 A _____ design piston is shorter on the two sides that are not thrust surfaces.
- 12 The outside diameter of the lands is about 0.02 to 0.04 in. smaller than the _____ diameter.
- 13 Piston ring _____ are located between the piston head and skirt.
- 14 Most pistons have horizontal separation slots that acts as _____.
- 15 The connecting rod is connected to a part of the crankshaft called a _____ bearing journal.
- 16 The connecting rod is connected to a part of the crankshaft called a crank throw, _____, or connecting rod bearing journal.
- 17 The width of the grooves, the width of the _____ between the ring grooves, and the number of rings are major factors in determining minimum piston height.

DOWN

- 1 _____ piston pins are free to "float" in the connecting rod and the piston.
- 2 To add strength, the silicon content is increased to about 16%, and the resulting piston is called a _____ piston.
- 3 Another name for the connecting rod bearing journal is the _____.
- 5 The _____ forms a movable bottom to the combustion chamber.
- 6 Another name for a piston pin is the _____.
- 7 The space in the ring groove above the ring is called the _____.
- 8 The piston is attached to the connecting rod with a _____.
- 9 A method of expansion control was devised using a _____ piston skirt.
- 10 _____ seal the small space between the piston and the cylinder wall, keeping the pressure above the piston.
- 11 The _____ side of the piston head has a greater area than the major side.