
Audio System Operation And Diagnosis

Chapter 30



http://janesnaideman.com

• •	_	_	_	_
AC	к	u	5	2

1	modulation waves are radio waves that have
	amplitude that can be varied, transmitted, and detected
	by a receiver.
5	is the number of times a particular waveform
	repeats itself in a given amount of time.
6	The purpose of any is to reproduce the original
	sound as accurately as possible.
8	A, which is a coil of wire, can also be used
	to reduce or eliminate radio interference.
11	is the term used to describe when
	information is added to a constant frequency.
14	A is the time and distance between two
	consecutive points, either high or low.
16	Ais a speaker designed to reproduce high-
	frequency sounds, usually between 4,000 and 20,000
	Hz.
17	Afilter is used to transfer higher frequency to
	smaller speakers.
18	A produces the lowest frequency of sounds,
	usually 125 Hz and lower.
19	Be careful when installing additional audio equipment o
	a GM vehicle system that uses a two-wire speaker
	connection called a system

DOWN

1	use an external power source and			
	produce superior performance.			
2	A capacitor provides electrical reserve			
	energy needed by the amplifier to provide deep base			
	notes.			
3	A is a measure of sound power, and it is the			
	faintest sound a human can hear in the midband			
	frequencies.			
4	All speakers used on the same radio or amplifier should			
	have the same internal coil resistance, called			
7	Ais designed to separate the frequency of a			
	sound and send a certain frequency range, such as low			
	bass sounds, to a woofer designed to reproduce these			
	low-frequency sounds.			
9	Frequency is measured in			
10	Another name for a powerline capacitor is			
	capacitor.			
12	When a high-frequency signal is transmitted through a			
	wire, the majority of it travels on the outside surface of			
	the wire, his is called			
13	The range of a typical device is 33 feet.			
15	recognition allows the driver of a vehicle to			
	perform tasks, such as locate an address in the			
	navigation system by using commands rather			

