


Emission Control Devices Operation and Diagnosis

Chapter 32



<http://jameshalderman.com>

ACROSS

- 3 A _____ contains a spring-type metallic disc or reed that closes under exhaust backpressure.
- 8 Most GM and many other vehicles use a _____ that contains a pulse-width modulated solenoid to precisely regulate exhaust gas flow and a feedback potentiometer that signals the computer regarding the actual position of the valve.
- 10 Excessive _____ emissions are controlled by the exhaust gas recirculation system and the catalytic converter.
- 11 A _____ pressure sensors monitors the rate with which vacuum increases in the system.
- 12 A _____ is an aftertreatment device used to reduce exhaust emissions outside of the engine.
- 13 The catalytic converter does not work when cold, and it must be heated to its _____-_____ temperature of close to 500°F (260°C) before it starts working at 50% effectiveness.
- 14 Measure the inlet and the outlet temperatures using an _____ thermometer.

DOWN

- 1 _____ systems were developed to ventilate the crankcase and recirculate the vapors to the engine's induction system so they can be burned in the cylinders.
- 2 The catalytic converter uses a _____, which is a chemical that helps start a chemical reaction but does not enter into the chemical reaction.
- 4 The recirculated exhaust gas is _____ and does not enter into the combustion process.
- 5 Many vehicles use a _____ pump as part of the evaporative control system diagnosis equipment.
- 6 _____ is an emission control system that lowers the amount of NOx formed during combustion.
- 7 The substrate is coated with a porous aluminum material called a _____, which makes the surface rough.
- 9 By a process called _____, the fuel vapor molecules adhere to the carbon surface.
- 12 Since the early 1990s, many converters contain _____, an element that can store oxygen.