


Diesel And Biodiesel Fuels

Chapter 7



<http://jameshalderman.com>

ACROSS

- 2 The _____ is a measure of the ease with which the fuel can be ignited.
- 6 _____ could include animal or fish oils from cooking.
- 7 The emission controls used on 2007 and newer diesel engines require the use of _____ for reliable operation.
- 8 _____ is the term most often used in Europe to describe straight vegetable oil.
- 10 _____ is the temperature below which the fuel would stop flowing.
- 11 _____ is one of the diesel fuel required characteristics.
- 13 _____ classifies diesel fuel by volatility into grades.
- 14 _____ is another name for regular diesel fuel.

DOWN

- 1 _____ is the name for No. 2 standard diesel outside of the United States.
- 2 _____ is the low-temperature point when the waxes present in most diesel fuels tend to form crystals that can clog the fuel filter.
- 3 _____ is a term used when the oil may or may not be pure vegetable oil.
- 4 _____ is standard No. 2 diesel fuel that contains up to 15% ethanol.
- 5 _____ is an arbitrary scale expressing the gravity or density of liquid petroleum products.
- 9 _____ is a domestically produced, renewable fuel that can be manufactured from vegetable oils, animal fats, or recycled restaurant greases.
- 12 Vegetable oil is a triglyceride with a glycerin component joining three hydrocarbon chains of 16 to 18 carbon atoms each, called _____.