


Clutches and Band

Chapter 7



<http://jameshalderman.com>

ACROSS

- 4 Ford Motor Company calls the first clutch the _____-_____.
- 5 Chrysler Corporation calls the first clutch the _____.
- 8 The _____ connect a member of the gear train to the transmission case.
- 14 While applying the clutch, there should be the proper _____ to get a good, smooth shift.
- 15 The neutral-to-drive and neutral-to-reverse shifts are called _____.

DOWN

- 1 Plates lined with friction material are called _____.
- 2 A _____ uses spring-loaded, rectangular struts in the face of one clutch ring, the pocket plate that can engage notches in the face of another ring, the notch plate.
- 3 Some new clutch designs use friction plates with _____.
- 6 GM and Toyota call the first clutch the _____.
- 7 The _____ connect the turbine shaft from the torque converter to the elements of the planetary gear train.
- 9 An _____ is tied hydraulically to the clutch or band servo, and absorbs fluid during the pressure buildup stage when a clutch or band applies.
- 10 While the clutch is applied, there should be sufficient _____ to transfer torque without slippage.
- 11 _____ shifting requires that one apply device be timed with the application of the apply device for the next gear range.
- 12 A _____ is an unlined plate that is wavy, not flat.
- 13 The unlined clutch plates are called _____.