Name_____

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

 Fixed drums are held on by a cotter key and spindle nut. A) True B) False 	1)
2) Old brake shoes are often returned to the manufacturer when new friction material is installed. These old shoes are usually called theA) core	2)
B) return	
C) deposit	
D) root	
 3) The drum brake on one side of a vehicle is dragging. Which of these could NOT be the cause? A) Sticking wheel cylinder piston B) Improper shoe adjustment C) Broken retracting springs D) Air in the system 	3)
4) What is the technician doing in this illustration?	4)



- A) Hold down spring removal/replacement
- B) Shoe return spring adjustment
- C) Shoe clearance adjustment
- D) Unbolting the shoe retainer

5) The first step in brake drum removal is to _____.

- A) mark the drum R or L
- B) loosen the parking brake cable
- C) remove the drum retaining device

D) remove the master cylinder cover to bleed off hydraulic pressure

1

5) _____

6) Technician A says that bolts are used to attach the wheel cylinder to the backing plate. Technician B says that clips are used to attach the wheel cylinder to the backing plate. Which technician is correct? 6) _____

7) _____

8)

9) _____

- A) Technician A only
- B) Technician B only
- C) Both technicians
- D) Neither technician
- 7) Technician A says that silicone brake grease can be used to lubricate the shoe contact ledges. Technician B says that synthetic brake grease, lithium brake grease, or anti-seize compound can be used as a brake lubricant. Which technician is correct?
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician
- 8) Technician A says that most experts recommend replacing all drum brake hardware including the springs every time the brake linings are replaced. Technician B says that the starwheel adjuster must be cleaned and lubricated to assure proper operation. Which technician is correct?
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician
- 9) Technician A says that brake drums should be labeled "left" and "right" before being removed from the vehicle so that they can be reinstalled to the same location. Technician B says that the holddown pins may have to be cut off to remove a worn brake drum. Which technician is correct?
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician
- - A) 1/2 in. (13 mm) B) 1/4 in. (7 mm) C) 1/8 in. (4 mm) D) 1/16 in. (2 mm)

Answer Key Testname: AT6_104B

> 1) A Page Ref: 1198 2) A Page Ref: 1203 3) D Page Ref: 1206 4) A Page Ref: 1199 5) A Page Ref: 1197 6) C Page Ref: 1202 7) C Page Ref: 1204 8) C Page Ref: 1195 9) C Page Ref: 1197, 1199 10) D Page Ref: 1200