
Automotive Technology 6th Edition Chapter 115 - Tire and Wheel Service Quiz 115B

## Name\_\_ \_\_\_\_\_

## MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

<ol> <li>What is the proper tightening sequence for lug nuts?</li> <li>A) Star (criss-cross) pattern</li> <li>B) Clockwise rotation</li> <li>C) Counterclockwise rotation</li> <li>D) None of these</li> </ol>	1)
<ul> <li>2) What is the term used to describe mounting a tire with the valve stem lined up with the dot painted on the tire?</li> <li>A) Match mounting</li> <li>B) Equal configuration</li> <li>C) Wheel balancing</li> <li>D) None of these</li> </ul>	2)
<ul> <li>3) Technician A says that most manufacturers recommend using anti-seize compound on lug studs when installing wheels. Technician B says that air impact wrenches are the best tool to tighten lug nuts. Which technician is correct?</li> <li>A) Technician A only</li> <li>B) Technician B only</li> <li>C) Both technicians</li> <li>D) Neither technician</li> </ul>	3)
<ul> <li>4) For best tire life, most vehicle manufacturers recommend tire rotation every</li> <li>A) 3000 miles</li> <li>B) 6000 miles</li> <li>C) 9000 miles</li> <li>D) 12000 miles</li> </ul>	4)
<ul> <li>5) Compressed nitrogen is sometimes used for tire inflation because it holds less moisture than compressed air.</li> <li>A) True</li> <li>B) False</li> </ul>	5)
6) When seating a bead of a tire, never exceed psi. A) 30	6)

- B) 40 C) 50
- D) 60



- A) Lateral runout
- B) Radial runout
- C) Tire balance
- D) Tire out-of-round

8) When installing a tire pressure monitoring system sensor on a wheel, the sensor should be	8)	
mounted		

7) \_\_\_\_\_

10) \_\_\_\_\_

- A) with the flat part of the sensor parallel to the center section of the rim
- B) with the flat part of the sensor facing the center section of the rim
- C) both A and B
- D) neither A nor B
- 9) Technician A says that it is recommended that the vehicle be driven less than 50 mph for the first
  9) \_\_\_\_\_\_
  50 miles to allow the tire to adhere to the wheel. Technician B says that sudden hard acceleration with newly mounted tires can cause the tire to change position on the wheel. Which technician is correct?
  - A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician

10) Proper tire inflation pressure information is found \_\_\_\_\_.

- A) on the driver's door or post
- B) in the owner's manual
- C) on the sidewall of the tire
- D) Both A and B

Answer Key Testname: AT6\_115B

> 1) A Page Ref: 1373 2) A Page Ref: 1378 3) D Page Ref: 1373 4) B Page Ref: 1375 5) A Page Ref: 1371 6) B Page Ref: 1379 7) A Page Ref: 1376 8) A Page Ref: 1378 9) C Page Ref: 1379 10) D Page Ref: 1370