ΓΙΡLE CHOICE. Choose the one alternative that best completes the statement of	or answers the question.
1) Commonly damaged areas of a vehicle during hoisting include	1)
A) rocker panels	
B) exhaust systems	
C) tires or body panels	
D) all of these	
2) Vehicle hoists are rated by	2)
A) maximum lifting capacity	
B) the maximum height a vehicle can be lifted	
C) both A and B	
D) neither A nor B	
3) Which symbol is used to indicate safe lifting points?	3)
A) Triangle	
B) Square	
C) Ĉircle	
D) None of these	
4) Proper lifting usually requires the vehicle to be	4)
A) centered in the stall	,
B) positioned with the front wheel centered on the tire pad	
C) both A and B	
D) neither A nor B	

8) Tall safety stands would be used to	8)
A) help support the vehicle when a major component is removed from the vehicle	
B) lift a vehicle	
C) lift a component such as an engine high off the ground	
D) Both B and C	
9) Many unit-body vehicles can be lifted at the	9)
A) steering rack	
B) front and rear control arms	
C) bumpers	
D) pinch welds	
10) The proper height for lifting should place the work area	10)
A) at chest level	
B) near the floor	
C) over the technicians head	
D) none of these	

Answer Key

Testname: AT6_11A

- 1) D Page Ref: 99
- 2) A Page Ref: 98
- 3) A Page Ref: 98
- 4) C Page Ref: 98
- 5) A Page Ref: 97
- 6) A Page Ref: 100
- 7) A Page Ref: 100
- 8) A Page Ref: 98
- 9) D Page Ref: 98
- 10) A Page Ref: 100