

Name \_\_\_\_\_

**MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.**

- 1) When assembling the pump, what is the alignment clamp used for? 1) \_\_\_\_\_
  - A) To help hold the pump while installing the seal
  - B) To guide the pump into the case
  - C) To align the pump halves while torquing the bolts
  - D) To help install the outer O-ring
  
- 2) Technician A says all gaskets should be discarded during teardown to keep the work area clean. Technician B says to keep the old valve body gaskets intact to make sure the replacement is a perfect match. Which technician is correct? 2) \_\_\_\_\_
  - A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
  
- 3) Technician A says that all friction and steel plates in a clutch pack should be replaced during an overhaul. Technician B says that the automatic transmission fluid cooler should always be flushed when a unit is rebuilt or replaced. Which technician is correct? 3) \_\_\_\_\_
  - A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
  
- 4) It is not possible to install the one-way clutch backwards. 4) \_\_\_\_\_
  - A) True
  - B) False
  
- 5) Why should red assembly lube be avoided? 5) \_\_\_\_\_
  - A) Can harm friction disks
  - B) Too slippery
  - C) Clogs filters
  - D) Looks like an ATF leak when it melts
  
- 6) A "fast learn" procedure using a scan tool is performed to re-set the \_\_\_\_\_. 6) \_\_\_\_\_
  - A) odometer settings
  - B) speedometer calibration
  - C) rear axle ratio
  - D) adaptive settings
  
- 7) The torque converter is normally reused when a transmission is rebuilt. 7) \_\_\_\_\_
  - A) True
  - B) False

8) Air pressure checking is used to test \_\_\_\_\_. 8) \_\_\_\_\_  
A) clutch packs  
B) TV adjustment  
C) vacuum modulators  
D) governors

9) Friction discs should be \_\_\_\_\_ before being installed. 9) \_\_\_\_\_  
A) sanded  
B) soaked in ATF  
C) surface roughed up  
D) all of these

10) All of these may be repaired with the transmission in the vehicle EXCEPT \_\_\_\_\_. 10) \_\_\_\_\_  
A) valve body  
B) pressure switches  
C) speed sensors  
D) friction discs

## Answer Key

Testname: AT6\_136B

1) C

Page Ref: 1731

2) B

Page Ref: 1727

3) B

Page Ref: 1732

4) B

Page Ref: 1730

5) D

Page Ref: 1731

6) D

Page Ref: 1733

7) B

Page Ref: 1725

8) A

Page Ref: 1729

9) B

Page Ref: 1729

10) D

Page Ref: 1723