

Name \_\_\_\_\_

**SHORT ANSWER. Write the word or phrase that best completes each statement or answers the question.**

1) Why is a 50/50 mixture of antifreeze and water commonly used as a coolant?

---

---

2) What are the differences among IAT, OAT, HOAT, and PHOAT coolants?

---

---

3) What is the difference between galvanic activity and electrolysis?

---

---

4) What are some of the heavy metals that can be present in used coolant?

---

---

5) What types of coolant are used in vehicles?

---

---

## Answer Key

Testname: SHORT 20

- 1) A 50/50 mixture provides the best combination of freezing protection and heat transfer ability of the coolant.  
Page Ref: 188
- 2) IAT contains silicate and phosphates and is used in vehicles older than 1996. OAT, HOAT, and PHOAT are used in many vehicles and include their own additive package.  
Page Ref: 189-190
- 3) Galvanic activity is voltage production without an outside source of voltage, whereas electrolysis is created when the vehicle has a poor ground connection.  
Page Ref: 193
- 4) Some of the heavy metals found in used coolant include lead, aluminum, and iron.  
Page Ref: 194
- 5) All factory installed coolant is ethylene-glycol based and currently includes: OAT, HOAT, and PHOAT formulations.  
Page Ref: 189-190