


Name \_\_\_\_\_

**MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.**

- 1) Technician A says that brake drums should be labeled "left" and "right" before being removed from the vehicle so that they can be reinstalled to the same location. Technician B says that the holddown pins may have to be cut off to remove a worn brake drum. Which technician is correct? 1) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician

- 2) What is the technician checking in this illustration? 2) \_\_\_\_\_



- A) Shoe diameter
  - B) Shoe-to-backing plate clearance
  - C) Shoe-to-drum clearance
  - D) Shoe conicity
- 3) Technician A says to use synthetic grease to lubricate the backing plate. Technician B says to use special lithium-based brake grease. Which technician is correct? 3) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
- 4) Technician A says that starwheel adjusters use different threads (left and right-handed) for the left and right sides of the vehicle. Technician B says that the threads and end caps of the adjusters should be lubricated with brake grease before being installed. Which technician is correct? 4) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician

- 5) Technician A says that many vehicle manufacturers recommend that wheel cylinders not be honed because of the special surface finish inside the bore. Technician B says that some experts recommend that the wheel cylinders be replaced every time the brake linings are replaced. Which technician is correct? 5) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
- 6) Technician A says that silicone brake grease can be used to lubricate the shoe contact ledges. Technician B says that synthetic brake grease, lithium brake grease, or anti-seize compound can be used as a brake lubricant. Which technician is correct? 6) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
- 7) Wheel cylinders are being discussed. Technician A says that if a wheel cylinder is not leaking fluid it is OK. Technician B says that wheel cylinders often require further inspection. Which technician is correct? 7) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
- 8) Old brake shoes are often returned to the manufacturer when new friction material is installed. These old shoes are usually called the \_\_\_\_\_. 8) \_\_\_\_\_
- A) core
  - B) return
  - C) deposit
  - D) root
- 9) Technician A says that when repairing brakes, it is a good practice to inspect the backing plate for a bent or cracked structure. Technician B says that the pads of the backing plate should be lubricated with heavy grease before installing new shoes. Which technician is correct? 9) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician
- 10) Technician A says to use masking tape temporarily over the lining material to help prevent getting grease on the lining. Technician B says that grease on the brake lining can cause the brakes to grab. Which technician is correct? 10) \_\_\_\_\_
- A) Technician A only
  - B) Technician B only
  - C) Both technicians
  - D) Neither technician