

Name _____

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

- 1) Commonly damaged areas of a vehicle during hoisting include _____. 1) _____
 - A) rocker panels
 - B) exhaust systems
 - C) tires or body panels
 - D) all of these

- 2) Vehicle hoists are rated by _____. 2) _____
 - A) maximum lifting capacity
 - B) the maximum height a vehicle can be lifted
 - C) both A and B
 - D) neither A nor B

- 3) Which symbol is used to indicate safe lifting points? 3) _____
 - A) Triangle
 - B) Square
 - C) Circle
 - D) None of these

- 4) Proper lifting usually requires the vehicle to be _____. 4) _____
 - A) centered in the stall
 - B) positioned with the front wheel centered on the tire pad
 - C) both A and B
 - D) neither A nor B

- 5) Most floor jacks have _____ casters. 5) _____
 - A) four
 - B) two
 - C) six
 - D) eight

- 6) Technician A says that a hoist can be stopped at any level as long as the safety latch engages. Technician B says that the vehicle should be hoisted to the top of the hoist travel for safety. Which technician is correct? 6) _____
 - A) Technician A only
 - B) Technician B only
 - C) Both technicians
 - D) Neither technician

- 7) When lowering a vehicle, _____. 7) _____
 - A) lower the vehicle slowly and make sure it remains stable
 - B) first engage the safety locks
 - C) both A and B
 - D) neither A nor B

8) Tall safety stands would be used to _____. 8) _____
A) help support the vehicle when a major component is removed from the vehicle
B) lift a vehicle
C) lift a component such as an engine high off the ground
D) Both B and C

9) Many unit-body vehicles can be lifted at the _____. 9) _____
A) steering rack
B) front and rear control arms
C) bumpers
D) pinch welds

10) The proper height for lifting should place the work area _____. 10) _____
A) at chest level
B) near the floor
C) over the technicians head
D) none of these