

Name _____

MULTIPLE CHOICE. Choose the one alternative that best completes the statement or answers the question.

- 1) It is not possible to install the one-way clutch backwards. 1) _____
A) True
B) False

- 2) Air pressure checking is used to test _____. 2) _____
A) clutch packs
B) TV adjustment
C) vacuum modulators
D) governors

- 3) Friction discs should be _____ before being installed. 3) _____
A) sanded
B) soaked in ATF
C) surface roughed up
D) all of these

- 4) The torque converter is normally reused when a transmission is rebuilt. 4) _____
A) True
B) False

- 5) A "fast learn" procedure using a scan tool is performed to re-set the _____. 5) _____
A) odometer settings
B) speedometer calibration
C) rear axle ratio
D) adaptive settings

- 6) Clutch pack clearance can be changed, if not correct, by using a selective _____. 6) _____
A) piston
B) pressure plate
C) snap ring
D) one of the above, depending on the unit

- 7) Technician A says all gaskets should be discarded during teardown to keep the work area clean. Technician B says to keep the old valve body gaskets intact to make sure the replacement is a perfect match. Which technician is correct? 7) _____
A) Technician A only
B) Technician B only
C) Both technicians
D) Neither technician

8) Technician A says that the torque converter should be separated from the flex (drive) plate before removing the automatic transmission/transaxle. Technician B says that the clutches should be installed "dry" when replacing the frictions and steels in a clutch pack. Which technician is correct? 8) _____

- A) Technician A only
- B) Technician B only
- C) Both technicians
- D) Neither technician

9) The transmission valve body should be installed using a small air ratchet. 9) _____

- A) True
- B) False

10) Steel discs should be _____ before being installed. 10) _____

- A) sanded
- B) surface roughed up
- C) cleaned
- D) all of these