

# Sealed Wheel Bearing Replacement

Meets ASE Task: A5 – F-6 – P-1

Name: \_\_\_\_\_ Date: \_\_\_\_\_ Time on Task: \_\_\_\_\_

Make/Model/Year: \_\_\_\_\_ VIN: \_\_\_\_\_

Evaluation (Enter number from 4, 3, 2, 1) : \_\_\_\_\_

- ☐ 1. Check service information for the specified replacement procedure for the vehicle being serviced. \_\_\_\_\_  
\_\_\_\_\_
- ☐ 2. Safely hoist the vehicle.
- ☐ 3. Remove the front wheel.
- ☐ 4. Remove the drive axle shaft hub nut.
- ☐ 5. Remove the front disc brake caliper.
- ☐ 6. Remove the rotor, the hub, and splash shield retaining bolts.
- ☐ 7. Mark the location of the hub and make certain the hub is loose on the steering knuckle.
- ☐ 8. Install the hub puller and remove the bearing and hub assembly.
- ☐ 9. Clean and lubricate hub bearing surface.
- ☐ 10. Install the hub and bearing assembly
- ☐ 11. Torque the drive axle shaft nut to specification.  
Specification = \_\_\_\_\_ (usually about 200 lb.-ft.)
- ☐ 12. Reinstall the rotor, caliper, and wheel.

